

Narrow woven  
**Reinforcements**



# Reinforcing Tapes

Article	Width mm	Thickness mm	Make-up per roll/m	Colours		Breaking load Newton	Extension at break per cent
---------	----------	--------------	--------------------	---------	--	----------------------	-----------------------------

## Topline Reinforcing Tapes, woven

<b>7209 PES</b>	1.00	0.37	1000	nat/black		134	12.3
<b>3623 PA</b>	2.25	0.42	750	natural		270	20.4
<b>9313 PES</b>	2.30	0.31	750	nat/black		194	17.1
<b>5968 PES</b>	2.38	0.38	500	nat/black		320	20.8

## Topline Reinforcing Tape, braided

<b>39073 PES</b>			750	natural		215	19.2
------------------	--	--	-----	---------	--	-----	------


## Topline Reinforcing Tapes, woven – non-adhesive or self-adhesive

Polyamide double cloth reinforcing tape, fine and very flexible

<b>27456 PA</b>	3.00	0.49	500	natural		181	22.1
<b>27456 PA</b>	4.00	0.47	300	natural		249	22.6

Widths available: 3 – 12 mm

Polyamide double cloth reinforcing tape, fine and very flexible, self-adhesive

<b>27222 PA</b>	4.00	0.47	400	nat/black		249	22.6
<b>27222 PA</b>	6.00	0.39	300	nat/black		325	22.7

Widths available: 3 – 12 mm (colour black in 4 and 6 mm)

## Strap Reinforcing and Shaping Tape

Thermoplastic strap reinforcing tape, self-adhesive, prong-proof

<b>7631</b>	4.00	0.71	50	natural		221	5.0
-------------	------	------	----	---------	--	-----	-----

Widths available: 3 – 20 mm

Strap reinforcing tape, prong-proof, very stiff finish, self-adhesive

<b>27793</b>	3.00	0.73	150	natural		165	4.2
--------------	------	------	-----	---------	--	-----	-----

Widths available: 3, 4 and 6 mm

Strap reinforcing tape, non-permanent shaping, self-adhesive



<b>41075</b>	6.00	0.45	100	natural		215	3.8
--------------	------	------	-----	---------	--	-----	-----

Widths available: 4 - 12 mm

Article	Width mm	Thickness mm	Make-up per roll/m	Colours		Breaking load Newton	Extension at break per cent
---------	-------------	-----------------	-----------------------	---------	--	----------------------------	-----------------------------------



## Woven Strap Reinforcing Tapes

### Polyamide double cloth reinforcing tape, prong-proof, non-adhesive or self-adhesive

<b>49110</b>	4.00	0.57	250	nat/black		228	29.3
<b>49111 self-adh.</b>	8.00	0.50	150	nat/black		390	29.9



Widths available: 3 – 50 mm

### Linen/Polyamide reinforcing tape, non-adhesive or self-adhesive

<b>50080</b>	4.00	0.63	500	natural		170	7.7
<b>50081 self-adh.</b>	6.00	0.65	50	natural		297	7.3

Widths available: 3 – 25 mm

### Polyamide reinforcing tape, prong-proof, non-adhesive or self-adhesive

<b>68950</b>	4.00	0.36	500	black		214	27.1
<b>43521 self-adh.</b>	8.00	0.31	250	natural		518	24.2

Widths available: 6 – 50 mm

### Very fine and strong Nylon tape with heat-sealed edges, self-adhesive

<b>3501</b>	10.00	0.16	150	nat/black		241	19.0
-------------	-------	------	-----	-----------	--	-----	------

Widths available: 6 – 50 mm

## Woven Reinforcing Tapes – for maximum performance

### High-tenacity Polyamide tape, prong-proof, self-adhesive, primer on reverse side

<b>57510</b>	10.00	0.32	75	nat/black		609	25.6
--------------	-------	------	----	-----------	--	-----	------

Widths available: 3 – 60 mm



# Woven Reinforcing Tapes

## Topline Reinforcing Tapes

A good quality topline tape must have the following properties to ensure best possible performance of the footwear.

- A high breaking load
- A proper stretch to ensure that the topline will not break during the lasting operation and to help keep the upper in shape and tight to the foot
- A high degree of flexibility to guarantee that the tape follows the various curves of the topline
- A minimal thickness to give the shoe a fine folded edge

## Strap Reinforcing and Shaping Tapes

Jaeger offers a variety of strong reinforcing tapes which are designed to retain the shape of the strap, both in production and in wear.

- The thermoplastic coating of Art. 7631 conforms to the shape of the last during the heatsetting process and ensures a durable bond with the upper and/or lining material. The short elongation of Art. 7631 keeps the shoe tight to the foot which is essential for high-heeled footwear.
- The stiff finish of Art. 27793 helps to keep the shape of the straps for shoes which are not heat-set
- Because of the special construction of Art. 41075 it is possible to give a modifiable shape to the strap.

## Prong-proof Strap Reinforcing Tapes

We offer a variety of strong and prong-proof reinforcing tapes with different coating options.

- Art. 49110, very strong
- Art. 43520/68950, very strong and very thin
- Art. 50080, very strong and short elongation

### Coating options:

- Self-adhesive coating
- Heat-sensitive coating
- Self-adhesive coating + primer on reverse side
- Centre coating (when used as lasting tape)
- Latex impregnation
- Non-fraying finish



### Gebrüder Jaeger GmbH

Otto-Hahn-Str. 7  
42369 Wuppertal  
Germany  
t +49 (0)202 24656-0  
f +49 (0)202 24656-39  
sales-germany@jaeger-ttc.com

### Jaeger Italia Srl

Via Emilia Romagna n° 96/98  
41049 Sassuolo (Mo)  
Italia  
t +39 0536 076168  
f +39 0536 076167  
sales-italy@jaeger-ttc.com

### Jaeger Iberica S.L

Calle X S/N. Pol. Ind. El Oliveral  
46190 Ribarroja de Túria, Valencia  
Spanien  
Tel. +34 963211082  
E-Mail sales-spain@jaeger-ttc.com

### Jaeger İzolasyon Bantları ve Yalıtım Elemanları Tic. Ltd. Şti.

Çınardere Mh. Gençlik Cd.  
No:17/A 34896  
Pendik / İstanbul, Turkey  
t +90 216 598 1388  
f +90 216 598 1388  
sales-turkey@jaeger-ttc.com

### Gebrüder Jaeger

**Austria GesmbH**  
Gewerbestraße 300  
8942 Wörschach  
Austria  
t +43 3682 24262  
f +43 3682 28232  
sales-austria@jaeger-ttc.com

### Jaeger Nordic AB

Bellevuevägen 55  
21619 Malmö  
Sweden  
t +46 40 128 707  
jonas.bostrand@jaeger-nordic.se

### Jaeger South Africa (Pty) Ltd

Unit 15A  
Growth Point Industrial Park  
1 Bell Street  
Meadowdale, Eden-vale, 1614  
South Africa  
Tel. +27 68 569 6391  
Fax + 49 202 24 656 995  
sales-south-africa@jaeger-ttc.com

For your single sourcing and total quality requirements

- Super Tack Tapes/Sheets
- Functional Elastics
- Woven Reinforcements
- Local Reinforcement



### Jaeger USA, Inc.

198, Pickering Road, Rochester  
New Hampshire 03867  
USA  
t +1 603 332 5816  
f +1 603 335 3608  
jus@jaeger-ttc.com

### Jaeger Rus Ltd.

v. Petushkova 8  
105425 Moskau  
Russia  
t +7 495 922 8354  
sales-russia@jaeger-ttc.com

### Jaeger Polska sp. z o.o.

ul. Żwirowa 1  
64-920 Piła, Polen  
Tel. +48 67 214 11 54  
Fax +48 67 214 10 89  
E-Mail info-jpl@jaeger-ttc.com

### Jaeger S.à.r.l.

10, rue Gutenberg  
67610 La Wantzenau  
France  
t +33 38815 0875  
f +33 38815 0895  
info-france@jaeger-ttc.com

### Jaeger Products PVT. LTD.

No: 60 & 61, Padavattamman  
Industrial estate, Pattaravakkam  
Chennai – 600098, India  
t +91 44 4950 2627  
baskar@jaegerindia.com